



TRT Crane Pads evenly distribute outrigger crane loads. Quality engineering ensures all TRT Crane Pads adhere to the CICA industry standards.

PAD-082-T

PAD WEIGHT: 2125kg

MINIMUM FOOT SIZE: 590mm x 590mm

MAXIMUM SPAN: 1000mm

MAXIMUM LOAD: 225T

GROUND PRESSURE RATING		
WIDTH (mm)		3400
LENGTH (mm)		2400
CONTACT AREA (m ²)		8.2
GROUND PRESSURE	kg / m ²	kPa
25 TONNE	3064	30
50 TONNE	6127	60
100 TONNE	12255	120
150 TONNE	18382	180
200 TONNE	24510	240
225 TONNE	27574	270

UNLESS OTHERWISE STATED

GENERAL TOLERANCES
 0.00 = ±0.05
 0.0 = ±0.2
 0 = ±0.5
 ANGLES 0 = ±0.5°

THIRD ANGLE PROJECTION
 SURFACE FINISH (µm)
 1.6

THIS DRAWING IS © COPYRIGHT AND IS THE PROPERTY OF TIDD ROSS TODD LTD. IT IS FURNISHED TO YOU FOR CONFIDENTIAL INFORMATION PURPOSES ONLY AND IS NOT TO BE DISCLOSED TO ANYONE ELSE OR USED FOR MANUFACTURING PURPOSES WITHOUT THE EXPRESS WRITTEN PERMISSION OF TIDD ROSS TODD LTD.

WELDING: ALL INFORMATION SHALL COMPLY WITH NZ/AS 1554:2000 PT 1 CATEGORY SP UNLESS OTHERWISE STATED AND SHALL BE WELDED TO A QUALIFIED PROCEDURE, BY A WELDER QUALIFIED FOR THE APPROPRIATE POSITION AND SUPERVISED BY A WELDING SUPERVISOR. WIRE BUFF ALL STEEL COMPONENTS PRIOR TO WELDING

REV	DATE	COMMENT	NAME

TIDD ROSS TODD LIMITED

48 Maui Street
 Hamilton
 New Zealand
 Ph: +64 7 849 4839
 Email: trt@trt.co.nz
 ISO 9001:2015

NAME	DATE	TITLE:
DRAWN JH	10/06/20	CRANE PAD 3400 X 2400 ASSY
CHK'D -	-	
APPV'D -	-	
DO NOT SCALE DRAWINGS IN mm's		STATUS - M
SHEET 3 OF 3		DWG NO. PAD-082
SCALE:1:22		REVISION A