

Tri/Tri Skeletal Crane Counterweight B-Double

Drawing reference 234-A1 W

Forward Length	A trailer = 7.1m B trailer = 8.8m
Deck Length	A trailer = 6.8m B trailer = 11.6m
Width	2.5m
Tare Weight	10,000kg approx.
Axle Spacing	1.25m
King Pin	2" bolt in
Skid Plate Height	1260mm TBC
Chassis	Fabricated I Beam construction from Grade 80 high tensile steel. Special headboard & locking mechanism for counterweights and jib sections to minimise additional load restraints.
Coaming Rail	Profiled Flat bar with pressed edge c/w rope rail.
Load Restraints	Rope rails on coaming rail. Tie down points for Slings.
Decking	Steel decking with non slip surface
Suspension	Heavy duty BPW air suspension.
Mounting brackets	Specially designed bollards and/or mounting modules are located on the trailer for the counterweights to be loaded. Mounts are designed for safe easy load/unload and securing of load.
Access to weights	A platform each side complete with handrail and steps allows access to tie down weights
Safety	Handrail system fitted to platform, easy load/unload of weights
Axles	6 of 22.5 BPW Disc braked axles - 10 stud axles with grease filled hub.
Rims	24 of 22.5 - 10 stud polished alloy wheels.
Tyres	24 of 22.5 – 11R tubeless radials.
Spare Tyre Mount	No spare or mount supplied to meet tare weight

Guards	Individual plastic.
Braking	To meet ADR regulations, EBS
Lighting	LED lighting system to meet ADR requirements.
Yard Release	Fitted on RHS.
Landing Legs	Jost wind up legs
Paint	Grit blasted, primed and painted in 2K paint system, electrostatically applied for full coverage.

Please Note: Specifications shown above for Australia, please contact us for specification for New Zealand and other countries.

Trailer Options

TRT has a wide range of standard and customisable options available for each trailer. These options are designed fit for purpose.

Design and Engineering

TRT has a full range of design and build capability. If you require a transport solution or have a specific purpose for your new trailer, TRT are able to work with you from initial sketches or specifications to create fully engineered design solutions for your payloads now and in the future.

Manufacturing

TRT design, fabricate and manufacture in house. TRT are accredited ISO 9001:2015, quality is critical to ensure your trailer will meet and in most cases exceed your requirements to minimise payback period. When you choose a trailer from TRT, it's for the long haul.



NEW ZEALAND

PHONE: +64 7 849 4839
 ADDRESS: 48 Maui St, Hamilton
 EMAIL: trailers@trt.co.nz
 WEB: www.trt.co.nz

AUSTRALIA

PHONE: 1800 802 912
 ADDRESS: 1028 Lytton Rd, Murarrie, QLD 4172
 EMAIL: trailers@trtaust.com.au
 WEB: www.trtaust.com.au